

NEW

Telstar[®] Boreas

Ultra Low Temperature Freezers

Environment friendly

Small footprint

Great cooling performance

Enhanced reliability

Low power consumption

Temperature uniformity



Main features

- High quality materials:
 - VIP insulation: provides better temperature uniformity and reduces external dimensions. More samples, less footprint.
 - Inner chamber entirely made in Stainless Steel.
 - Five foamed Stainless Steel inner doors.
- Ecological gases: use of 100% pure natural refrigerants, allows easy service and contributes to preserving the environment.
- Low sound level and low power consumption, thanks to new Boreas design and improved cooling system.
- Enhanced reliability: new ergonomic handle and frame structure, new door sealing, new system for filter replacement,...
- Standard features include heated pressure equalization valve, two sample throughputs (plus 2 more pre-cut), 4 shelves with 5 individual internal doors, RS485 and remote alarm, wheels.
- Robust packaging with pallet with ramp for easy unloading

Technical data

CONSTRUCTION	Units	Boreas Upright			Boreas Chest		
Cabinet Material	Internal	Full A-304 Stainless Steel interior					
	External	Polyester coated exterior					
Insulation Material		VIP panels and Polyurethane foam					
Sample throughputs		2 standard ports (+ 2 pre-cut)					
Shelves, inner doors		Standard 5 foamed Stainless Steel inner Doors, 4 Shelves			Rigid PU inner covers		
Refrigerants		1 st Stage: R290 2 nd Stage: R170					
TECHNICAL SPECIFICATION	Units	U445	U570	U830	C370	C620	C820
External dimensions (WxDxH) ^(*)	mm	650x821x2012	790x821x2012	1080x821x2012	1267x872x1073	1742x872x1073	2142x872x1073
Internal Volume	L	445	570	830	370	620	820
Footprint	m ²	0,53	0,65	0,89	1,1	1,5	1,9
Vials Capacity (2ml)	unit	30.000	40.000	60.000	28.000	44.800	61.600
Weight (uncrated/crated)	Kg	270/302	293/328	352/392	180/200	220/250	285/325
Distance Between shelves		Adjustable every 10mm. By default 290mm			-		
Cooling performance	°C	-55°C to -86°C (factory set point is -80°C)					
Mains/Power supply	V/Hz	230V 50 Hz					
Power consumption ⁽¹⁾	kWh/day	14	14,4	14,8	18,2	19	19,8
Pull down time ⁽²⁾	min	200	240	280	200	240	280
Warm up time -80°C to -50°C ⁽³⁾	min	240	240	240	90	90	90
Warm up time -50°C to 0°C ⁽³⁾	min	900	900	900	800	800	800
Door open recovery time ⁽⁴⁾	min	10	10	10	-	-	-
Temperature uniformity ⁽⁵⁾	°C	3	3	3	2	2	2

NOTE:

Values above based in average data from 5 units batch.

(*) Dimensions without considering handle and hinge. Total width dimensions add 77 mm in upright model

Test Conditions: (Tamb: 22°C; RH:50±5%)


(1) ECO mode SP -80°C. Unit empty. Normal cycling without door openings.

(2) OPT mode SP -80°C. Unit empty.

(3) Measurement in Sensor Block.

(4) OPT mode SP -80°C. Unit empty. 3rd inner door opened during 60s.

(5) OPT mode SP -80°C. According to Telstar test protocol.



ISO 9001: Certified Company

FL-ULT-BOREAS-EN-0318

Telstar reserves the right to improvements and specifications changes without notice.

SPAIN

Headquarters

Av. Font i Sagué, 55
08227 Terrassa (Spain)
T +34 937 361 600
F +34 937 861 380

Santibáñez de Béjar, 3
08042 Madrid
T +34 913 717 790
F +34 913 717 791

JAPAN

Azbil Corporation
Tokyo Building,
2-7-3 Marunouchi, Chiyoda-ku,
Tokyo 100-6419,
T +81 3 6810 1000
F +81 3 5220 7270

NORTH AMERICA

1504 Grundy's Lane
Bristol PA 19007
T +1 (215) 826 0770
F +1 (215) 826 0222

CHINA

No. 30 Jin Wen Road,
Zu Qiao Airport Industrial Park,
Pudong District
201323 Shanghai
T +86 21 58 093 731
F +86 21 58 092 857

marketing@telstar.com
www.telstar.com